

LHP2

2 Ports Profibus DP/FMS Isolation Hub



Introduction

The LHP2 is an industrial isolation hub which designed specially for extension of profibus cable transmission. It can extend double communication distance (depend on rate) to realize electrical isolation between multiple fieldbus nodes, has the function of very strong anti interference. At the same time realize signal regeneration and increase the number of nodes and change network topology, The product can be placed directly behind the PROFIBUS master station, single cable convert into another cables.

The LHP2 supports 2 independent PROFIBUS data cable interface. Complete electrical isolation between each other, any one electric interface data input will be output from the other electrical interface. The products have fault intelligent cut function, when one section of fieldbus network has failure, another section can not be affected. The product supports point to point network structure.

The product is made by our original proprietary technology, data transparent transmission, switch the direction of data automatically, without any of the settings. Support all PROFIBUS speeds, rate adaptation. Solves the problem of the extending distance transmission. The products inherit and keep all the advantages of the PROFIBUS, achieve long distance transmission, electric and ground isolation and reduce interference. The products solve the problem of electromagnetic interference, ground loop interference and lightning damage. At the same time, the products have the following advantages: industrial design, low power consumption, isolation protection, fault intelligent cut, relay alarm output, IP30 protection, aluminum case, 35mm DIN-rail installation, wide power supply (DC10-36V) input, dual redundancy power supply etc.

1. Support PROFIBUS full rates (9.6K-12M), rate adaptation, data transparent transmission, nanosecond signal delay
2. Support the double extension of PROFIBUS cable transmission distance (depend on rate)
3. Support point to point network topology structure
4. Electrical interface supplied by independent power supply module, completely isolated between profibus and profibus, and profibus and equipment; at the same time adopt photoelectric isolated technology, separate internal communication and data signal interference, effectively protect communication equipment from power ground loop and surge
5. Electric interface provides 1500W anti lightning surge protection of every line, 15KV electrostatic protection, prevention of total interference, and self-recovery over-current protection function



6. Has the fault intelligent cut function, power monitoring, relay automatic alarm function
7. Rich LED status indicator, all-round display profibus state
8. Two independent power supply redundancy, wide power supply(DC10-36V), DC1500V power supply isolation, with 1A reverse connection protection function
9. Industrial design, no fan, low power consumption, strong anti magnetic field, anti radiation and anti interference function
10. Corrugated metal case with high strength,IP30 protection,35mm DIN-Rail

Specification

Electrical interface

Interface type: DB9 Fe-male, compliant with EN 50170 PART1 standard

Data rate: 9.6kBit/s、19.2 kBit/s、45.45kBit/s、93.75kBit/s、187.5kBit/s、500kBit/s、1.5MBit/s、6MBit/s 、12MBit/s,Rate adaptation

Signal delay(electrical port):100ns

Offer 1500W anti lightning surge protection, 15KV electrostatic protection, prevention of total interference, and self-recovery over-current protection function

Wire Terminal Resistance: None

Power and Protection

Input Voltage:DC24V(DC10V-36V)

Input Current:100mA@24V

Voltage protection: offer L1+/M/L2+ reverse connect protection

Current protection: 1A(short-circuit protection)

Relay alarm output: electrical port fault and fiber link fault alarm output

Contact rating:DC30V@1A, AC120V@1A

Environmental

Operating Temperature: -10 to 70℃ (-40℃ to85℃ optional)

Ambient Relative Humidity: ≤ 95% (non-condensing)

Storage Temperature: -45℃ to 85℃

Mechanical

Dimensions:136mm×52mm×105mm (H×W×D)

Casing: IP30 protection, Aluminum metal case with high strength

Installation: 35mm DIN-Rail

Weight :800g

Industrial standard

EMI: EN55022 1998, Class A

EMS:

EN61000-4-2 (ESD), Criteria B, Level 4

EN61000-4-3 (RS), Criteria A, Level 2

EN61000-4-4 (EFT), Criteria B, Level 4

EN61000-4-5 (Surge), Criteria B, Level 2

EN61000-4-6 (CS), Criteria B, Level 2

En61000-4-8 (PFMF), Criteria A, Level 3



The relationship between PROFIBUS transmission rate and distance:

The following table is the relationship between the Profibus rate and transmission distance (theoretical value), the actual transmission distance is also associated with the field networks. This device supports 0-12M rate, it could extend the double cable transmission distance (dependent on rate).

Rate (K)	12000	6000	3000	1500	500	187.5	93.75	45.45	19.2	9.6
Distance (m)	100	100	100	200	400	1000	1200	1200	1200	1200

Topology structure

This series of products support point to point network topology

Applications

Electric power, transportation, energy, monitoring and industrial control and so on.

Order Information

Model	Specifications	unit
LHP2	Industrial PROFIBUS DP/FMS Isolation Hub, 2 independent electrical port, support point to point network topology	pcs